

HIDROTECHNICS PREVENT VIBRATIONS THAT OCCUR IN CONSTRUCTIONS**Muminov Oybek Alisher ugli**

Doctorate, Fergana polytechnic institute. Republic of Uzbekistan

Maksudov Rustam Ismoilovich

Assistant, Fergana polytechnic institute. Republic of Uzbekistan

<https://doi.org/10.5281/zenodo.7315841>

Abstract. *The preservation of the hydrotechnical structures from the vibration phenomenon is due to the Reserve work, which is carried out taking into account the circumstances associated with an increase or decrease in the flow in the project, an increase in the flood arrival time, a complete cessation of the water discharge pipeline, these works are completely received from the vibration phenomenon.*

Keywords: *cavitation, erosion, vibration, thermal efficiency, multi-phase liquid, dynamics.*

ГИДРОТЕХНИЧЕСКАЯ ПРЕДОТВРАЩЕНИЯ ВИБРАЦИИ, ВОЗНИКАЮЩИЕ В КОНСТРУКЦИЯХ

Аннотация. *Сохранность гидротехнических сооружений от явления вибрации обусловлена резервными работами, которые выполняются с учетом обстоятельств, связанных с увеличением или уменьшением расхода в проекте, увеличением времени прихода паводка, полным прекращением трубопровода для сброса воды, эти работы полностью получено из-за явления вибрации.*

Ключевые слова: *кавитация, эрозия, вибрация, тепловая эффективность, многофазная жидкость, динамика.*

INTRODUCTION

Finding the normal suction height of HES turbines, the emergence of cavitation processes at heights above or below this suction height, causes a meeting of vibrations of the HES and its construction. As a result of the deepening of the working wheel, the vibration of the entire system is observed, which leads to the penetration of cavitation into erosion. Such changes davriy will require that there will be repair work in progress. But as it turned out, in order to eliminate the vibration effect due to the absorption of cavitation erosion, it is useful to make a small deepening of the working building, provided that the working wheel is repaired.

MATERIALS AND METHODS

In order to protect erosion objects, such as landscaping or cavitation, producing manual farming. As more and more people leave their homes, they increasingly turn to us.

$$K > K_{кр}$$

Here: K is the cavitation parameter, K_{KR} is the cavitation parameter, which is critical. For some types of energy sinks and flow separators, K_{KR} values are given in. From this it can be seen that the less the tension to the extinguishers leads to a decrease in its K_{KR} coefficient, which means that it improves the cavitation properties of the extinguisher, thereby allowing it not to suffer cavitation even at very high speeds, but this situation leads to a decrease in the energy absorption properties of the extinguisher.

Science of water problems are still needed, has not reached the level of detection of various types of temporary injuries through the accounting of the growth process. But with the help of calculations it is possible to make reliable decisions on the protection of structures from vibrations.

In all of the above water bodies and pipes, various dissolved substances in running water, solid granules, whitewash in nature pure water itself is much less than threeaydi. Small vibrations in the water also lead to large fluctuations, so the fluid under consideration forms a complex multi-phase liquid. In the works of the above scientists and in the works of other authors, the methods that determine the rotational motion in water discharges required accuracy, otherwise the expected result in the design, exploitation of the gidroinshoot will not be obtained. The nature and legality of the currents coming out of the pipes and from the water dumps, along the pipe, into circulation, has not been fully studied. There is no stagnation of flow in connection with the occurrence of cross-circulation in the pipes conducting a water-carrying vortex.

RESULTS

The flow is transformed and flows with a spiral shape over the entire length of the pipe. The rotation axis of the spiral current is have, first the rotation axis is tilted and the swirling pinwheel looks. Then, under the influence of an irregular current, the swirling coil breaks down and rotates together with the current. After rotation, a few large swirls form in the stream, and this condition is called a division of swirls. The process of whirling and the division of the current into several streams occurs through the dynamics of the emergence of large energy. This process occurs through speed pulsations, and in the flow mode, enhanced turbulence occurs. The stagnation in the stream disappears and a cross-circulatory flow occurs, the flow type changes to the circulating stream.

Any type of current is divided into two characteristic spheres: The Central sphere with a whirlpool (Whirlpool core), that is, the sphere with a large whirlpool, that is, the sphere with a small Whirlpool, which is outside the sphere. The swirling field is a non-standard field of flow, in this area there are excitation, the deviation of the flow from the symmetry axis is observed, and as a result of this, the circulation is burned, and the centrifugal force field that stabilizes the flow is burned. The flow passes from the symmetrical form to the spiral form, without being able to suppress non-symmetrical excitation.[1,2]

As a result of the subsequent reduction in circulation, the circulatory flow ends completely and becomes a weak circulating current.High-speed pipe and as a result of a decrease in the hydrodynamic pressure of flowing streams in the canl causes the release of oxygen from the water. This process creates a two-phase flow consisting of water and air.

DISCUSSION

Due to a decrease in pressure in the air mixture in the water in the tapered pipe, a cavitation process occurs, which leads to a violation of the hydro technical structure by removing the pulsation and vibration gel. As an example, we can see that the construction of the 185m dam on the project was planned at the Hidrotechnical complex. From the process of exploitation, when the pressure reaches 105m, dangerous situations begin to arise in the water discharge plant. When the flow rate reached 25 m/s, the stagnant movement of the flow began, and in the water discharge system, a 5.5-point vibration process began.[3,4] As is known, cavitation is a murracean process, cavitation produces pulses and vibrations. And these processes completely change the flow regime, that is, the flow passes from a calm state to a complex developed turbulent state. In the stream there are swirls, circulatory States relative to the arrow. In such cases, as a result of interaction,a rise in temperature in the flow is observed. To characterize the cavitation prosses, we use the coefficient of cavitation.

$$K = \frac{H_{\text{хар}} - H_{\text{кр}}}{v_{\text{хар}}^2 / 2g}$$

At constant temperature, through static and dynamic pressures, constant pressure in the flow occurs, or there is a decrease in pressure. Due to the decrease in pressure, the vapor bubbles in the stream begin to form, increasing along the flow and turning into caverns. Due to the fact that the pressure in the caverns is greater than the pressure in the liquid, it exits to the surface of the flow crack, there is a phenomenon of pulsation and cavitation in the flow, vibration in the pipes begins.[5,6,7,8,9]

CONCLUSION

In addition to the fact that the cavitation process produces vibration gel, the migration along the cavitation stream causes the formation of non-condensing gas bubbles, caverns in the stream. Gas bubbles in the stream, Caverns go up, narrow and then burst. Such non-stationary gas bubbles also appear in the walls of the caverns, due to low pressure near the wall.

REFERENCES

1. Madaliev, M. E. U., Maksudov, R. I., Mullaev, I. I., Abdullaev, B. K., & Haidarov, A. R. (2021). Investigation of the Influence of the Computational Grid for Turbulent Flow. Middle European Scientific Bulletin, 18, 111-118.
2. Maqsudov, R. I., & qizi Abdukhalilova, S. B. (2021). Improving Support for the Process of the Thermal Convection Process by Installing. Middle European Scientific Bulletin, 18, 56-59.
3. ugli Mo'minov, O. A., Maqsudov, R. I., & qizi Abdukhalilova, S. B. (2021). Analysis of Convective Finns to Increase the Efficiency of Radiators used in Heating Systems. Middle European Scientific Bulletin, 18, 84-89.
4. Усаров, М. К., and Г. И. Маматисаев. "Вынужденные колебания коробчатой конструкции панельных зданий при динамических воздействиях." Проблемы механики 2 (2010): 23-25.
5. Nosirov A.A., Nasirov I.A. Simulation of Spatial Own of Vibrations of Axisymmetric Structures EUROPEAN MULTIDISCIPLINARY JOURNAL OF MODERN SCIENCE <https://emjms.academicjournal.io>
6. Akramov, A. A. U., & Nomonov, M. B. U. (2022). Improving the Efficiency Account Hydraulic of Water Supply Sprinklers. Central Asian Journal of Theoretical and Applied Science, 3(6), 364-370.
7. Shavkatjon o'g'li, T. B. (2022). Proving The Inequalities Using a Definite Integral and Series. Texas Journal of Engineering and Technology, 13, 64-68.
8. Rashidov, Y. K., & Ramankulov, S. A. (2021). Improving the Efficiency of Flat Solar Collectors in Heat Supply Systems. CENTRAL ASIAN JOURNAL OF THEORETICAL & APPLIED SCIENCES, 2(12), 152-159
9. Malikov, Z. M., & Madaliev, E. U. (2019). Mathematical simulation of the speeds of ideally newtonovsky, incompressible, viscous liquid on a curvilinearly smoothed pipe site. Scientific-technical journal, 22(3), 64-73.

10. Nosirov A.A., Nasirov I.A. Simulation of Spatial Own of Vibrations of Axisymmetric Structures EUROPEAN MULTIDISCIPLINARY JOURNAL OF MODERN SCIENCE <https://emjms.academicjournal.io>
11. Shavkatjon o'g'li, T. B. (2022). SOME INTEGRAL EQUATIONS FOR A MULTIVARIABLE FUNCTION. Web of Scientist: International Scientific Research Journal, 3(4), 160-163.
12. Abobakirovich, A. B., Sodikovich, A. Y., & Ogli, M. I. I. (2019). Optimization of operating parameters of flat solar air heaters. Вестник науки и образования, (19-2 (73)), 6-9.
13. Usmonova, N. A. (2021). Structural Characteristics of the Cavern at a Fine Bubbled Stage of Cavitation. Middle European Scientific Bulletin, 18, 95-101.
14. Nasirov Ismail Azizovich. On The Accuracy of the Finite Element Method on the Example of Problems about Natural Oscillations. EUROPEAN MULTIDISCIPLINARY JOURNAL OF MODERN SCIENCE <https://emjms.academicjournal.io>
15. Мадхадимов, М. М., Абдулхаев, З. Э., & Сатторов, А. Х. (2018). Регулирования работы центробежных насосов с изменением частота вращения. Актуальные научные исследования в современном мире, (12-1), 83-88
16. Madaliev, E. U., & qizi Abdukhalilova, S. B. (2022). Repair of Water Networks. CENTRAL ASIAN JOURNAL OF THEORETICAL & APPLIED SCIENCES, 3(5), 389-394.
17. Abdullayev, B. X., & Rahmankulov, S. A. (2021). Modeling Aeration in High Pressure Hydraulic Circulation. CENTRAL ASIAN JOURNAL OF THEORETICAL & APPLIED SCIENCES, 2(12), 127-136.
18. Abbasov, Y. S., & ugli Usmonov, M. A. (2022). Design of an Effective Heating System for Residential and Public Buildings. CENTRAL ASIAN JOURNAL OF THEORETICAL & APPLIED SCIENCES, 3(5), 341-346.
19. Умурзакова, М. А., Усмонов, М. А., & Рахимов, М. Н. (2021). АНАЛОГИЯ РЕЙНОЛЬДСА ПРИ ТЕЧЕНИЯХ В ДИФФУЗОРНО-КОНФУЗОРНЫХ КАНАЛАХ. Экономика и социум, (3-2), 479-486.
20. Mo'minov, O. A. O'tbosarov Sh. R. "Theoretical analysis of the ventilation emitters used in low-temperature heat supply systems, and heat production of these emitters" Eurasian journal of academic research, 495-497.
21. Namdamalievich S. A. Determination of the deposition of particles contained in the water passing through the sump well //Central asian journal of theoretical & applied sciences. – 2022. – Т. 3. – №. 6. – С. 244-251.
22. Рашидов, Ю. К., Орзиматов, Ж. Т., Эсонов, О. О. Ў., & Зайнабидинова, М. И. К. (2022). СОЛНЕЧНЫЙ ВОЗДУХОНАГРЕВАТЕЛЬ С ВОЗДУХОПРОНИЦАЕМЫМ МАТРИЧНЫМ АБСОРБЕРОМ. Scientific progress, 3(4), 1237-1244.
23. Усаров, Махаматали Корабоевич, and Гиёсиддин Илхомидинович Маматисаев. "КОЛЕБАНИЯ КОРОБЧАТОЙ КОНСТРУКЦИИ КРУПНОПАНЕЛЬНЫХ ЗДАНИЙ ПРИ ДИНАМИЧЕСКИХ ВОЗДЕЙСТВИЯХ." Научный форум: технические и физико-математические науки. 2019.Рашидов, Ю. К., Орзиматов, Ж. Т., & Исмоилов, М. М. (2019). Воздушные солнечные коллекторы: перспективы применения в условиях Узбекистана. ББК 20.1 я43 Э 40.

24. Usmonova, N. A., & Khudaykulov, S. I. (2021, April). SPATIAL CAVERNS IN FLOWS WITH THEIR PERTURBATIONS IMPACT ON THE SAFETY OF THE KARKIDON RESERVOIR. In E-Conference Globe (pp. 126-130)
25. Hamdamaliyevich S. A., Nurmuhammad H. Analysis of Heat Transfer of Solar Water Collectors //Middle European Scientific Bulletin. – 2021. – Т. 18. – С. 60-65.
26. Xamdaliyevich, S. A., & Rahmankulov, S. A. (2021, July). Investigation of heat transfer processes of solar water, air contact collector. In E-Conference Globe (pp. 161-165)
27. Madaliev, M. E. U., Rakhmankulov, S. A., & Tursunaliyev, M. M. U. (2021). Comparison of Finite-Difference Schemes for the Burgers Problem. Middle European Scientific Bulletin, 18, 76-83
28. Сагторов, А. Х., Акрамов, А. А. У., & Абдуразаков, А. М. (2020). Повышение эффективности калорифера, используемого в системе вентиляции. Достижения науки и образования, (5 (59)), 9-12.
29. Abdukarimov, B. A., O'tbosarov, S. R., & Tursunaliyev, M. M. (2014). Increasing Performance Efficiency by Investigating the Surface of the Solar Air Heater Collector. NM Safarov and A. Alinazarov. Use of environmentally friendly energy sources.
30. Madraximov, M. M., Nurmuxammad, X., & Abdulkhaev, Z. E. (2021, November). Hydraulic Calculation Of Jet Pump Performance Improvement. In International Conference On Multidisciplinary Research And Innovative Technologies (Vol. 2, pp. 20-24).